

13 H1650-W Tabletop High Speed Micro Centrifuge

The high-speed micro centrifuge offers triple protections against over-speed, door lid and improper operation, and 7 types of rotors are available for free choice.



Technical Parameters

Model	H1650-W	Noise	□67dB (A)
Order No.	0203167000	Power supply	AC220V 50/60Hz 3A
Max.speed	16500rpm	Power consumption	250W
Max.RCF	18360xg	Dimensions (WxDxH)	265x335x220mm
Max.capacity	12x5ml	Package Size (WxDxH)	322x452x268mm
Speed accuracy	±30rpm	Net weight	11kg
Time range	1min to 99min		

Rotor Optional

No.1 	No.2 	No.3 	No.4 
Order No: 0301809100 Speed: 16500rpm RCF: 18360xg Capacity: 12x1.5ml Adapter: 0304805005(0.2ml) 0304805004(0.5ml)	Order No : 0301810500 Speed: 16500rpm RCF: 18360xg Capacity: 18x0.5ml	Order No: 0301809200 Speed: 12000rpm RCF: 10142xg Capacity: 12x5ml Adapter: 0304806104(1.5ml) 0304806103(0.5ml)	Order No : 0301856300 Speed: 13000rpm RCF: 16170xg Capacity: 24x1.5ml Adapter: 0304805004(0.5ml) 0304805005(0.2ml)
No.5 	No.6 	No.7 	
Order No: 0301809400 Speed: 15000rpm RCF: 13800xg Capacity : 3x8x0.2ml PCR	Order No: 0301856400 Speed: 12000rpm RCF: 14800xg Capacity: 12pcs capillary	Order No: 0301856300 Speed: 12000rpm RCF: 14800xg Capacity: 24 pcs capillary	