

41 CTK32/CTK32R Automatic Decapping Centrifuge



Features

- ✧ 100% Automatic decapping for vacuum blood collecting tube .
- ✧ Suitable for the tube length of 100mm & 75mm.
- ✧ Large LCD, AC inverter motor, high accuracy of speed control, offering quick acceleration and deceleration.
- ✧ Automatic calculation of RCF.
- ✧ Effective deduction of vibration, accommodating the function of self balance.
- ✧ Electronic door locking system for safe operation.

Rotor optional

 Order No: 0307853591 Max.speed: 4000rpm Max.RCF: 2980xg Max. number of tubes: 32 pcs (Φ13x75/100mm)	 Tube carrier Order No: 0303853595 Max.capacity: 4x8x7/5ml (Vacuum blood collection tube)	 Order No: 0310853592 Adapter: (Φ13x75/100mm)
--	--	---

Technical Parameters

Model	CTK32	CTK32R
Order No.	020584350	0204141100
Max. Speed	4000rpm	4000rpm
Max. RCF	2980xg	2980xg
Max. Tubes	32pcs (Φ13x75/100mm)	32pcs (Φ13x75/100mm)
Speed Accuracy	+/-30rpm	+/-30rpm
Time Setting Range	1s to 99min59s	1s to 99min59s
Temperature Range	/	-20~40°C
Control Accuracy	/	+/-1°C
Compressor set	/	High performance and environment-friendly compressor set(R134a)
Noise	≤65dB(A)	≤62dB(A)
Power Supply	AC220V±22V 50Hz 5A	AC220V±22V 50Hz 10A
Power Consumption	370W	1200W
Dimensions (W x D x H)	470x560x380mm	470x730x380mm
Package Dimension (W x D x H)	547x727x422mm	547x960x422mm
Net Weight(kg)	38kg	70kg